



Mini Cam

USB, 300k Pixels

**For great visual imaging, it's simple to get started –
and even easier to enjoy sharing the results.**

Model
460668

The MANHATTAN® Mini Cam helps improve online communications and experiences with high-quality photos and video. With simple, one-button operation and easy-to-use software, its 300k-pixel (software interpolated) CMOS lens captures crisp and clear images and smooth, steady video to share with family and friends. The compact size, attractive finish and Plug and Play installation make it a good accessory for desktop and notebook PCs.

Software-Simplified Settings and Operation

With the AMCap software, videos and still frames are easily captured and shared. Common file formats allow you to save AVI video, BMP and JPG images. The software allows you to configure the camera manually or to take advantage of its automated features

Compact Size for Easy Storage and Transport

Light weight and small size are just two key features that benefit frequent travelers. These units are compact and light, perfect for people that are often on the go.

Adjustable Clip Base for Easy Attachment to Laptop or Desktop

Clip the unit to your monitor, or use the base to set down on your desk. The hinged clip allows you to place the camera where you need to and adjust the camera as needed.

Ready to Use

Simple-to-install software means you just plug in the device and let Windows do the work for you.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty – the strongest quality commitment anyone can make.





LIFETIME
WARRANTY

Model
460668

Features

- Capture and share photos and video — software simplifies settings and operation
- Compact size for easy storage and transport
- Adjustable clip base for easy attachment to laptop or desktop systems
- Ready to use — Plug and Play installation; Windows compatible
- Lifetime Warranty

Specifications

GENERAL

- Resolution: true 100k-pixel resolution (software interpolated to 300k-pixel)
- CIF CMOS sensor
- USB 1.1 interface
- Bus powered
- Lens: F2.2 1/4-inch lens with focus ring
- Focus distance: 30 mm to infinity
- Min. illumination: 2.5 lux
- Viewing angle: 55 degree horizontal
- Camera controls: Saturation, Contrast, Sharpness
- Transmission speed: 320 x 240 at 30 fps; 640 x 480 at 15 fps
- Built-in image compression
- Color compensation: automatic and manual
- White balance: automatic and manual
- File formats: AVI, JPG, BMP
- Operational temperature: 0 – 40°C
- Storage temperature: -20 – 60°C
- Imperial dimensions:
 - Overall: 6 x 1.5 x 3.25 in. (L x W x H)
 - Cable length: 56 in.

- Metric dimensions:
 - Overall: 15.25 x 3.8 x 8.25 cm (L x W x H)
 - Cable length: 142.25 cm
- Weight (imperial): 2.4 oz.
- Weight (metric): 68 g

SYSTEM REQUIREMENTS

- IBM PC-compatible computer or notebook with USB port
- Pentium 200 or higher CPU
- Windows 98SE/Me/2000/XP
- 20 MB of HDD space
- CD-ROM drive
- VGA display card for DirectX

PACKAGE CONTENTS

- Mini Cam
- User manual
- Driver/application CD


MANHATTAN
BRINGING COMPUTERS TO LIFE

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.

Copyright © 2005 MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

MH-460668-DS-0806-01

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>