


# WHITE-RODGERS WALL THERMOSTATS


## HEATING/COOLING AND COOLING ONLY ASTRO\* STATS WITH SELECTOR-SWITCHES

- DUSTPROOF SEALED MERCURY CELLS OR SNAP-ACTION CONTACTS WITH DUSTCOVER
- BEIGE CASE WITH GOLD TONE DIAL
- POSITIVE CONTACT SNAP-SWITCHES ON SUBBASE
- BIMETAL THERMOMETER
- CLEAR FACEPLATE - REMOVABLE FOR EASY CLEANING
- HEATING AND COOLING ANTICIPATORS PROVIDE NARROW DIFFERENTIAL CONTROL OF ROOM TEMPERATURE




P574

Part No.: 1D56-310  
1F56-301  
1F56-444  
1E56-444




P574

1D56-301 SHOWN



P574


1F56-444 SHOWN



P577

1E56-444 SHOWN

## ASTROSTATS WITH SNAP ACTION SWITCH




P578

1D30-316 SHOWN

- SNAP ACTION CONTACTS WITH DUST COVER
- NON-SUSCEPTIBLE TO SLIGHT JARS AND VIBRATIONS
- IDEAL FOR MOBILE HOME USE
- HEATING AND/OR COOLING ANTICIPATORS PROVIDE A NARROW DIFFERENTIAL CONTROL OF ROOM TEMPERATURE

Part No.: 1D30-316  
1C30-302

## HEAT PUMP THERMOSTAT



P583

- MANUAL CHANGEOVER
- DUAL MERCURY CELL ARRANGEMENT ON A SINGLE BI-METAL PROVIDES CONTROL WITHOUT COMPLICATED GEAR AND LEVER ARRANGEMENTS
- THERMOSTAT MOUNTS TO SUBBASE WITH POSITIVE CAPTIVE SCREWS
- SUBBASE TERMINAL SCREWS SPACED AND IDENTIFIED FOR EASY INSTALLATION

Part No.: 1F58-058

# WHITE-RODGERS WALL THERMOSTATS


## COMFORT-SET 70 SERIES SINGLE STAGE DIGITAL THERMOSTATS

### STANDARD FEATURES:

- Large, easy-to-read display
- Electronic temperature accuracy
- Adjustable room temperature calibration
- B&O terminals
- Millivolt compatible
- Battery powered for maximum compatibility (2 "AAA" batteries included)

**Single Stage  
Non-Programmable**

**Part No.: 1F78-144**



P4558

**Single Stage  
2 Programs**

**Part No.: 1F78-151**

- Choice of 5/2 day programming or non programmable
- 4 time and 4 temperature settings per program for heating and cooling
- Meets California Building Code, Title 24
- Energy savings up to 33%


## COMFORT-SET 80 SERIES SINGLE STAGE DIGITAL THERMOSTATS

### STANDARD FEATURES:

- 60% larger LCD with improved contrast for easier reading
- Lighted display for easier low-light viewing
- Permanent program retention during power loss
- Air filter change indicator (optional)
- Simple menu to activate optional features
- Soft-touch keypad
- Maintains room temperature differential within 1 degree
- Display temperature recalibration (+/-4°)
- Powerful next-generation microprocessor
- Fast (FA) or slow (SL) heating cycle anticipation
- B&O terminals Compressor lockout protection
- Millivolt Compatible
- Electric heat option

**Single Stage  
Non-Programmable**

**Part No.: 1F86-244**



P4557

# WHITE-RODGERS WALL THERMOSTATS

## COMFORT-SET 80 SERIES SINGLE STAGE DIGITAL THERMOSTATS (cont)

### STANDARD FEATURES:

- Choice of 5/1/1 day or 7 day programmable or non-programmable
- 4 time and 4 temperature settings per program (heat & cool)
- Energy savings up to 33%
- Patented pre-programmed software simplifies time and temperature programming
- Indefinite setpoint Hold or programmable timed Hold up to 8 hours
- Temporary temperature override until next program period
- Dual-Powered...choice of battery-powered or hardwired, for all single stage applications
- Selectable Energy Management recovery
- Meets ENERGY STAR® specifications
- Meets California Building Code, Title 24

**Single Stage  
2 Programs**

**Part No.: 1F80-261**

## COMFORT-SET 90 SERIES SINGLE STAGE DIGITAL THERMOSTATS

### STANDARD FEATURES:


- Choice of 7 or 5/1/1 day or 7 day programmable or non-programmable
- 4 time and 4 temperature settings per program (heat & cool)
- Energy savings up to 33%
- Patented pre-programmed software simplifies time and temperature programming
- Large Comfort-View™ luminescent display
- Permanent program retention
- Vacation programming
- Air filter change indicator
- Daylight Savings Time quick-change button
- Temporary temperature override from 15 minutes to 19 hours or indefinite setpoint hold
- Display temperature recalibration (+/-5°)
- Maintains room temperature differential within .8 degree
- Automatic Heat/Cool System Changeover
- Selectable Energy Management Recovery
- Built-in system and thermostat diagnostics
- Digital-signal remote sensors (optional)
- Meets ENERGY STAR® specifications
- Meets California Building Code, Title 24
- Compressor lockout protection
- Millivolt compatible
- Electric heat option

**Single Stage  
3 Programs**

**Part No.: 1F90-371**

**Single Stage  
7 Programs**

**Part No.: 1F97-371**



P4556

---

# WHITE-RODGERS WALL THERMOSTATS

---

## COMFORT-SET 90 SERIES MULTI STAGE & HEAT PUMP DIGITAL THERMOSTATS

### STANDARD FEATURES:

- 7-day programming
- Four pre-programmed time/temperature periods per day
- Vacation Programming button
- Programmable fan continuous in any period
- Programmable fan on/off delays
- Separate set-up menus: Installer menu, User menu, Keypad lockout (total/partial) menu
- Large Comfort-View™ display and lighted keypad
- Permanent program retention – no batteries required
- Daylight Savings Time quick-change button
- Air filter change indicator
- Remote sensing (optional)
- Outdoor temperature sensing (optional)
- Multi-stage, heat pump, or single stage up to 3-stage heat/2-stage cool
- Auto-changeover
- EMR (*Energy Management Recovery*)
- Meets ENERGY STAR® specifications
- Meets California Building Code, Title 24
- Compressor lockout/Auxiliary run time
- Adjustable differential
- Telephone access run program (X10 module required)

### Heat Pump

- Heat pump warm air start
- Energy Source Optimizer selects heat pump or fossil fuel

**Part No.: 1F94-371**

### Multi Stage


**Part No.: 1F95-371**

- Ignition control reset


# TOTALINE THERMOSTAT GUARDS

## THERMOSTAT GUARDS

- Metal: beige
- Plastic: beige or clear
- Sizes fit most thermostats
- Solid and ring bases
- Have key lock
- Virtually tamper proof



**Metal**



**Plastic**

### Metal

WIDTH (in.)	HEIGHT (in.)	DEPTH (in.)	BASE	STYLE	PART NO.
3-7/8	3-1/2	2-1/2	Solid	Beige	P269-0010
5-1/4	4-5/8	3	Solid	Beige	P269-0011
5-1/4	4-5/8	3-1/4	Ring	Beige	P269-0012
6-3/8	3-1/2	3	Solid	Beige	P269-0013
6-3/8	3-1/2	3-1/4	Ring	Beige	P269-0014
6	3-3/16	3-1/8	Ring	Beige	P269-0015
6-1/4	4-3/4	3	Solid	Beige	P269-0016
7-1/4	5-3/8	3-1/2	Solid	Beige	P269-0017
6-3/4	4-1/4	3-9/16	Ring	Beige	P269-0018


### Plastic

WIDTH (in.)	HEIGHT (in.)	DEPTH (in.)	BASE	STYLE	PART NO.
3-7/8	3-1/2	2-1/2	Solid---	Clear-	P269-0001
3-7/8	3-1/2	2-1/2	Solid	Beige	P269-0002
5-1/4	4-5/8	3	Solid	Clear	P269-0003
5-1/4	4-5/8	3-1/4	Ring	Clear	
5-1/4	4-5/8	3	Solid	Beige	P269-0004
5-1/4	4-5/8	3-1/4	Ring	Beige	
6-3/8	3-1/2	3	Solid	Clear	P269-0005
6-3/8	3-1/2	3-1/4	Ring	Clear	
6-3/8	3-1/2	3	Solid	Beige	P269-0006
6-3/8	3-1/2	3-1/4	Ring	Beige	
8-1/4	5-3/8	3-1/2	Ring	Clear	P269-0007
8-1/4	5-3/8	3-1/2	Ring	Beige	P269-0008

# MISCELLANEOUS PARTS

## MISCELLANEOUS PARTS

### ROOM AIR CONDITIONER SERVICE CORDS




- 1/4 IN. QUICK CONNECT TERMINALS ON POWER LEADS
- RING TERMINAL ON GROUND WIRE
- IVORY COLOR EXCEPT 51PC CORDS ARE GRAY

P402

FIGURE	WIRE GAUGE	AMPS	VOLTS	LENGTH (in.)	PART NO.
A	14	15	125	93	51SA400353
B	14	15	250	66	52SQ402334
D	14	20	125	60	51CM400964
	12			113	60AA400094

FIGURE	WIRE GAGE	AMPS	VOLTS	LENGTH (in.)	PART NO.
E	14	20	250	82	52CQ400994
	12			66	51CM400974
G	12	30	250	82	52CQ401004

### ROOM AIR CONDITIONER FILTER




P729

The 51YA680001 polyurethane foam replacement room air conditioner filter measures 22-3/4 in. x 14-1/2 in. x 1/4 in. thick. It can be trimmed to fit most RAC's in use today.

**Part No.: 51YA680001S**

# TEMPERATURE ACTUATED SWITCHES


## CONTROL BULB



- CONTROL BULB WELLS FOR USE WITH TEMPERATURE CONTROLLERS
- BUSHING INCLUDED

FOR BULB DIA. (in.)	DIMENSIONS (in.)				THREAD SIZE NPT	PART NO.
	A	B	C	D		
5/16	13.0	11.5	1.2	.4	1/2-14	HL79PZ001
3/8	6.3	5.0	.7	.4	1/2-14	30HH406102
3/8	7.6	5.8	1.4	.4	1/2-14	HL79ZZ002
1/2	8.7	4.2	3.7	.7	1/2-14	HL79MZ001
1/2	8.7	4.2	3.7	.7	3/4-14	HL79MZ005
1/2	5.7	4.2	.7	.7	1/2-14	HL79MZ007

## AQUASTAT CONTROLLERS



P4320

### Part No. P672-L4006

- TOTALLY ENCLOSED MICRO SWITCH SNAP-ACTING SWITCHES OPERATE ON TEMPERATURE RISE TO SET POINT.
- VISIBLE CONTROL POINT SCALE AND EXTERNAL ADJUSTMENT SCREW PERMIT EASY SETTING.
- HORIZONTAL OR VERTICAL INSERTION AND DIRECT OR WELL IMMERSION OF SENSING ELEMENT.


### Part No. P672-L6006C

- OPERATE IN RESPONSE TO TEMPERATURE CHANGES IN HYDRONIC HEATING SYSTEMS.
- PROVIDES SPDT SWITCHING FOR THREE-WIRE APPLICATIONS.
- COMBINES CIRCULATOR CONTROL WITH HIGH AND LOW LIMITS.
- HORIZONTAL OR VERTICAL SURFACE MOUNTING.
- VISIBLE CONTROL POINT SCALE AND EXTERNAL ADJUSTMENT SCREW PERMIT EASY SETTING.

### Part No. P672-L7124U UNIVERSAL OIL ELECTRONIC AQUASTAT CONTROLLER

- PROVIDES ELECTRONIC TEMPERATURE SENSING IN A UL LIMIT-RATED CONTROL WITH A SINGLE SENSING PROBE.
- CONTROLS CIRCULATOR, OIL BURNER, AND BOILER TEMPERATURE.
- REPLACES THE L8124A, L8124C, L8148A CONTROLLERS.
- THE L7124U HAS A CASE THAT CAN BE CONVERTED FOR EITHER HORIZONTAL OR VERTICAL MOUNTING.


PART NO.	HONEYWELL PART NO.
P672-L4006A	L4006A1009
P672-L4006B	L4006B1007
P672-L6006C	L6006C1018
P672-L7124U	L7124U1003



P4321

# TEMPERATURE ACTUATED SWITCHES

## SWITCHING RELAYS



P4325

### Part No. P673-RA889A SWITCHING RELAY (HYDRONIC)

- HIGH LOAD SWITCHING RELAY.
- TROUBLESHOOTING LED.
- REPLACEABLE TRANSFORMER FUSE.
- LONG LIFE DC RELAY DRIVE CONTROL TECHNOLOGY.
- RELAY FOR USE WITH EXTERNAL 24 VAC OR 24 VDC SUPPLY, WITH LINE-VOLTAGE CONTROL, OR WITH INTERNAL 24-V TRANSFORMER SUPPLY.

### Part No. P673-R8845A UNIVERSAL SWITCHING RELAY (HYDRONIC)

- REPLACEABLE, SOCKETED RELAY.
- TWO TROUBLESHOOTING LED'S.
- PUSH-TO-TEST BUTTON.
- REPLACEABLE TRANSFORMER FUSE.
- LOW VOLTAGE CONTACTS FOR POWERPILE APPLICATIONS.
- RELAYS CAN BE USED WITH EXTERNAL 24-VAC OR 24-VDC SUPPLY, LINE-VOLTAGE CONTROL, OR WITH INTERNAL 24-V TRANSFORMER.

PART NO.	HONEYWELL PART NO.
P673-RA889A	RA889A1001
P673-R8845A	R8845U1003



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>