

# AVR-5308CI

AV Surround Receiver

# DENON



.Network

Reference, Next Generation HD AV Surround Receiver featuring Advanced Connectivity, Wi-Fi Network Audio Streaming and an interface that enhances your level of entertainment enjoyment.



## Bullet points

### Sophisticated Construction for the Ultimate A/V playback



- Fully separated Audio, Video, Power Amplifiers and Power Supplies allow for a cleaner and clearer signal path
- High current Toroidal Power Supply to drive discrete mono block amplifier channels
- 5 individual transformers to supply power to each discrete circuit
- Direct Mechanical Ground to minimize mechanical vibration from transformer and radiators
- All new circuit layouts that shorten audio and video signal paths for best picture and sound
- Gold plated wide pitch speaker terminal
- THX Ultra2 certified 150W x 7ch power amplifier

### Dynamic Discrete Surround Circuit, D.D.S.C.-HD

- Discrete Devices for ultimate performance in each circuit block
- 3 All New 32-bit floating point DSPs
- Master clock design for more accurate processing and less jitter noise
- Burr-Brown Audio DACs in differential mode (2 per audio channel) on all output channels (12)
- Advanced AL24 processing provides more dynamic range
- Dolby TrueHD and dts-HD Master Audio decoders

### Newly improved Audyssey MultEQ XT

- New tower type microphone for more accurate measuring
- Up to eight measurement points
- New filtering ALFC (Adaptive Low Frequency Correction) for higher resolution processing in the low frequency band.

### Full 10-bit processing video circuit

- Realta sX2 HQV processing for i/p and scaling
- HD/SD video noise reduction functionality
- Multi Cadence Detection for accurate i/p conversion
- 1080p/24fps pass through
- Analog video to HDMI scaling up to 1080p
- HDMI to HDMI scaling up to 1080p
- Deep Color up to 36-bit and xvYCC broader color space support
- Discrete construction and circuitry for highest quality video processing
- 12-bit/216-MHz video encoder and decoder with NSV



### Digital Media Connectivity

- Network Audio and Photo Streaming
  - Playback and control music files from PC and DLNA Servers
  - AAC, WMA, MP3, FLAC, WAV file support
  - Connect to over 7,000 internet radio stations
  - JPEG Photo slideshow
  - Rhapsody music online ready
- Connect to your network via Ethernet or Wi-Fi (802.11 b/g compatible)
- iPod audio, photo and video playback (optional ASD-1R/3N/3W)
- Mass storage support USB for audio and photo playback
- XM Ready, HD Radio built-in
- Compressed Audio Restorer to enhance digital music files

### Ease-of-Use


- New user interface for easy operation, setup and digital media browsing
- Album art support (iPod/Network/USB)
- Title text (iPod/Network/USB/XM/HD radio)
- Multi language support
- Available for 1080p HDMI



\*Sample image of new GUI

### Multi-Zone Capabilities

- Three Analog and One Digital, Four Zone multi-source capability
- Digital to analog conversion for multi-zone output
- Analog to digital conversion for multi-zone digital output
- Dual HDMI outputs
- Zone 2 OSD with text, Album art is also available
- Independent zone 2 component output
- Dual component outputs for main zone
- BNC connectors for component input/output
- IR Remote in/out ports
- +12V, 250mA trigger x 4 outputs
- RS-232C control x2
- IP control
- Optional RC-7000CI/7001RCI 2-way control ready
- Audyssey Pro Installer Ready
- Web setup, save and load all settings via Ethernet



### Input / Output terminals

| IN                           | Terminal                      | Count |
|------------------------------|-------------------------------|-------|
| IN                           | HDMI                          | 6     |
|                              | Component                     | 6     |
|                              | S-Video                       | 8     |
|                              | Composite                     | 8     |
|                              | Analog audio (Tuner included) | 11    |
|                              | Analog EXT. Input             | 7.1ch |
|                              | Digital OPTICAL               | 5     |
|                              | Digital COAXIAL               | 4     |
|                              | Digital COAXIAL BNC           | 2     |
|                              | Denon Link                    | 1     |
|                              | Ethernet                      | 1     |
|                              | Wi-Fi                         | 1     |
| OUT                          | USB                           | 2     |
|                              | Dock control for iPod         | 1     |
|                              | HDMI Monitor                  | 2     |
|                              | Component Main Monitor        | 2     |
|                              | Zone 2 Monitor                | 1     |
|                              | S-Video REC                   | 3     |
|                              | Monitor / Zone 2              | 1/1   |
|                              | Composite REC                 | 3     |
|                              | Monitor / Zone 2              | 1/1   |
|                              | Analog audio REC              | 3     |
|                              | Zone 2 / Zone 3               | 1/1   |
|                              | Analog Preout                 | 9.3ch |
| Digital OPTICAL REC          | 2                             |       |
| Digital OPTICAL Zone 2       | 1                             |       |
| Digital OPTICAL REC / Zone 4 | 1                             |       |

### Specifications

| Power Amplifier Section |   |
|-------------------------|---|
| Rated output            | *THD figures are power amp stage values.              |
| Front                   | 150 W + 150 W<br>(8 ohms, 20Hz - 20kHz, 0.05% THD)    |
| Center                  | 150 W<br>(8 ohms, 20Hz - 20kHz, 0.05% THD)            |
| Surround                | 150 W + 150 W<br>(8 ohms, 20Hz - 20kHz, 0.05% THD)    |
| Surround Back           | 150 W + 150 W<br>(8 ohms, 20Hz - 20kHz, 0.05% THD)    |
| General                 |   |
| Power supply            | AC 120 V, 60 Hz                                       |
| Dimensions (WxHxD)      | 434 x 217 x 500 mm<br>17-3/32" x 8-17/32" x 19-22/32" |
| Weight                  | 28.5 kg, 62.8 lbs                                     |



• Design and specifications are subject to change without notice.  
 • Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.  
 • DTS is a registered trademark & the DTS logos and symbol are trademarks of DTS, Inc.  
 • HDCD®, High Definition Compatible Digital® and Microsoft® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.  
 • "DCDI™" is a trademark of Faroudja, a division of Genesis Microchip Inc.  
 • Audyssey MultEQ is a trademark of Audyssey Laboratories. MultEQ and the Audyssey MultEQ logo are trademarks of Audyssey Laboratories, Inc.  
 • NSV and Sub Alias Filter are registered trademarks of Analog Devices, Inc.  
 • ©2007 XM Satellite Radio Inc. All rights reserved.  
 • HD Radio™ Technology Manufactured Under License From iBiquity Digital Corporation. iBiquity Digital, the HD Radio logo, and the HD logo are registered trademarks of iBiquity Digital Corporation.  
 • HD Radio™ is a trademark of iBiquity Digital Corporation. U.S. and Foreign Patents."

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>